



X-MILL 600
ALL IN ONE



X-MILL 600

- 5 axes simultaneous milling with B axis rotation range up to $\pm 30^\circ$
- Massive iron cast for better stability
- High performance Jäger spindle with 2.5kW of power
- 2 microns repetition accuracy
- Automatic tool changer for 12 tools
- Unrivaled milling results of abutment, implant bar and implant bridge



Technical parameters

Name: X-MILL600 industrial milling center

Weight: 850kg

Max power: 6.5kW

Number of axis: 5 axis

Processing mode: wet milling

Max feed rate: 6000mm/min

Tool changing mode: automatic

Processing materials: CoCr/NEM, titanium, PMMA, wax, glass ceramics, hybrid ceramics

Dimension (L*W*H): 1110*820*1820(mm)

Input voltage: AC220V

Spindle power: 2.5kW

Travel range: XYZ: 320/130/150mm
A: 360° B: $\pm 30^\circ$

Max speed: 60,000rpm

Tool magazine capacity: 12

Spindle cooling: water cooling

Processing time: Crown: 30 min abutment: 50min. bar: 2h



Professional Service Team



Online Support



Seasonal On-site Technical Support



Add: 2nd Floor, 1st building, No.88, North Zhuguang Rd, West Area, Honghualing Industrial Park, Nanshan District, Shenzhen, China

Tel: +86-755 8600 1804
E-mail: xtcera@xianton.com

Fax: +86-755 8600 1486
Web: en.xtcera.com